

Inspiration



Manufactured in France

Multi-temperatures cabinet

Small size

Service Pack



Built-in and flush-fitted, multi-temperatures cabinet, for serving wine







Technical specifications

Equipment Standard shelves









Sliding wine service area **ACMSFRVB**



ACMSIW

Sliding wine service area ACMSFRVW



ACMSI-DEMI 5 bottles

Equipment

Optional shelves







Storage shelf 22 bottles

29 bottles maximum* Capacity

Temperature · Default setup temperature: 8-18°C / 46-64°F

> ·Temperature setting range from 5°C to 20°C / 41- 68°F (5-10°C/ 41-50°F for the lower part and 15-20°C/59-68°F for the upper part).

Design · 4 doors options: full glass door, stainless steel glass

door, technical solid door and technical glass door (Reversible integrated glass door with soft close and door stop)

·Lock (except technical door)

·LED screen with backlit capacitive keys

· Amber inner lighting : atmosphere lighting with the light strip and 2 LEDs

·3 lighting options: permanent, open door, disabled)

·Amber screen display

Accessories

· 2 sliding shelves with Mains du Sommelier (possible adjustment of the position of the MDS, on the front)

·1 half shelf and 1 sliding wine service area

·Light oak and black glossy front

·Open / close locking notch

· 6 removable bottles identifiers per sliding shelf

·1 erasable felt-tip marker

·1 microfiber cloth

·1 key ring

Equipement ·Charcoal filter (with counter)

> ·Low-emissivity glass and argon gas between the 2 glasses (in glass door or full glass finish)

· 4 adjustable feet

·Condensate drip tray at the back

Regulation

·Electronic regulation

· Display of the real temperature inside the cabinet

· Display standby mode, possible

·Visual alarm: carbon filter

·Visual and audible alarms: temperature malfunction, sensor fault, open door

· Automatic defrost

Technologies Cold production: Static

Insulation type:

Cords: CE/US/UK/JA/AU/CH/C6/CN

Hot production: Heating element

Hot release: Automatic/ threshold: adjustable

Inner material: **Exterior coating material:**

HDF (High Density Fiber) melamine-faced panels

Stucco aluminium

PU Foam (59mm)

^{*}Traditional Bordeaux format



General features

| | Full Glass door/ stainless steel glass door | Technical glass door | Technical solid door |
|--------------------------------------|--|--|-----------------------|
| Empty wine cabinet net weight (kg) | 54 | 53 | 50 |
| Equipped cabinet net weight (kg) | 64 | 63 | 60 |
| Gross weight packaged (kg) | 77 | 76 | 73 |
| Dimensions H x W x D (mm) | 810-880x557-594**x597 | 810-880x557-594**x597 | 810-880x557-594**x597 |
| Dimensions packaged (mm) | 980x645x630 | 980x645x630 | 980x645x630 |
| Specific features of the decor panel | | Thickness: 20mm maximum / Weight: 12kg maximum | |

^{**}With fillers

Energy efficiency & Consumption

| Cords | 230V-50Hz (R600a) | 230V-50Hz (R600a) |
|--|-------------------|----------------------|
| Type of door | Full Glass/Glass | Technical solid door |
| Energy efficiency class | G | F |
| Annual energy consumption AEC (Kwh/year) | 125 | 99 |
| Sound emission (dB(A)) | 38 | 38 |
| Sound emission Class | С | С |
| Ambient operating temperature (°C/°F) | 12-35/54-95 | 12-35/54-95 |
| Useful volume (litres) | 9 |)4 |

NB: To guarantee the proper functioning of the wine cabinet, the top and bottom ventilation strips must not be covered in any way.

Inspiration, in a few words...

Understated & Elegant

The heart of the home, the kitchen is no longer reserved just for cooking. A place to gather and spend time together, it is open to all the family and often friends too. The kitchen has become a place where good times are shared, things are created, ideas germinate and chemistry happens...



