




ÌÌ

YEAR

Manufactured in France 1 temperature cabinet Small size

Service Pack





Equipment Standard shelves



Sliding shelf ACMSIB 6 bottles



Sliding wine service area ACMSERVB 11 bottles

Half shelf ACMSI-DEMI 5 bottles

Equipment **Optional shelves**



Storage shelf AXIHB 22 bottles



Sliding shelf ACMSIW 6 bottles

Sliding wine service area

ACMSERVW

11 bottles

Storage shelf AXIHW 22 bottles

Technical specifications

Capacity	28 bottles maximum*	
Temperature	•Default setup temperature: 12°C/5 •Temperature setting range from 5 ^o	
Design	 4 doors options: full glass door, stainless steel glass door, technical solid door, technical glass door (reversible integrated glass door with soft close and door stop) Lock (except technical door) LED screen with backlit capacitive keys 	 Amber inner lighting: atmosphere lighting with the light strip and 2 LEDs 3 lighting options: permanent, open door, disabled Amber screen display
Accessories	 2 sliding shelves with Mains du Sommelier (possible adjustment of the position of the MDS, on the front) 1 half shelf and 1 sliding wine service area Light oak and black glossy front 	 6 removable bottles identifiers per sliding shelf 1 erasable felt-tip marker 1 microfiber cloth 1 key ring
Equipement	•Charcoal filter (with counter) •Humidity cassette with clay ball	 Low-emissivity glass and argon gas between the 2 glasses (in glass door or full glass finish) 4 adjustable feet Condensate drip tray at the back
Regulation	 Electronic regulation Display of the real temperature inside the cabinet Possible humidity display Display standby mode, possible 	 Visual and audible alarms: temperature fault, sensor fault and open door Visual alarms: humidity fault and carbon filter change Automatic defrost Frost protection thermostat (double protection)
Technologies	Cold production: Cords: Hot production: Hot release: Inner material: Exterior coating material: Insulation type:	Static/ Compressor R600a CE/US/UK/JA/AU/CH/C6/CN Heating element Automatic/ threshold: adjustable Stucco aluminium HDF (High Density Fiber) melamine-faced panels PU Foam (59mm)

General features

	Full Glass door	Stainless steel glass door	Technical glass door	Technical solid door
Empty wine cabinet net weight (kg)	54	54	53	50
Equipped cabinet net weight (kg)	64	64	63	60
Gross weight packaged (kg)	77	77	76	73
Dimensions H x W x D (mm)	810-880x557-594**x597	810-880x557 -594**x597	810-880x557-594**x597	810-880x557-594**x597
Dimensions packaged (mm)	980x645x630	980x645x630	980x645x630	980x645x630
Specific features of the decor panel		Thickness:	20mm maximum / Weight: 12k	g maximum

**With fillers

Energy efficiency & Consumption

Cords	230V-50Hz (R600a)	230V-50Hz (R600a)	230V-50Hz (R600a)
Type of door	Full Glass door	Stainless steel glass door/ technical	Technical solid door
Energy efficiency class	G	G	F
Annual energy consumption AEC (Kwh/year)	125	125	99
Sound emission (dB(A))	38	38	38
Sound emission Class	С	С	С
Ambient operating temperature (°C/°F)	12-35/54-95	12-35/54-95	12-35/54-95
Useful volume (litres)		94	

NB: To guarantee the proper functioning of the wine cabinet, the top and bottom ventilation strips must not be covered in any way.

Inspiration, in a few words...

Understated & Elegant

The heart of the home, the kitchen is no longer reserved just for cooking. A place to gather and spend time together, it is open to all the family and often friends too. The kitchen has become a place where good times are shared, things are created, ideas germinate and chemistry happens...



