



Premium Pack









Maturing cabinet, for ageing or serving wine

1 temperature cabinet

YEAR WARRANTY

Technical Specifications

Manufactured in France

Capacity Temperature and Hygrometry

106 or 124 maximum bottles*

· Setting range from 6 to 18°C · At 12°C, independently regulated hygrometry at 70%

Design

- · Triple glazed and anti UV Full Glass door with argon gas. Not reversible. Right or left opening > Choice on order
- Inner lighting: ambiance lighting by 4 LED under each shelf and 2 LED under the control panel (3 options: permanent, when opening door,disabled). 3 levels of light intensity
- · Handle integrated in the door profile
- · LED screen with sensitive keys

Sliding shelf ACMSR

Standard shelf



9 Bordeaux bottles

7 Bordeaux bottles + 2 Magnum bottles

Regulation and equipement

- · Electronic regulation
- · Internal display and settings
- Temperature display
- · Hygrometry display,non adjustable.
- · Display only at 12°C
- · Alarms in case of dysfunction (open door, sensor fault, temperature dysfunction, hygrometry dysfunction, need to fill the humidity tank, need to replace charcoal filter)
- · Default ECO mode (= screen saver)

- · Automatic defrost
- · On/Off/ switch

Large size

- · Active charcoal filter 150x150 mm
- · 4 adjustable shock absorbing feet + 4 embellishments
- · Condensate discharge pipe
- · Autonomous hygrometry regulation tank «Hygrocontrol System». Patented system
- · Frost protection thermostat

Covering 6 covering available





Grey

Farth



Châtaigner









Marbre Palazio



Touch

Accessories

· 11 sliding shelves + 1 fixed, with black tinted ash front

Sliding shelves equipped with a soft close device

· 8 mains du Sommelier at the bottom of the cabinet

· 6 removable bottle identifiers per sliding shelf

· 1 erasable felt tip marker

· 1 key ring

·1 microfiber cloth

Technologies

Cold production:

Cords:

Mixed air/ Variable speed compressor R600a gas CE/US/UK/JA/AU/CH/C6

Heat production: Heat release:

Automatic 45W resistor

Resistance

Aluminium

Exterior coating material:

HPL panel (High pressure laminated)

Insulation type:

Inner material:

Injected polyurethane foam (59 mm)





General features

	Full Glass door
Gross weight packaged (kg)**	340
Net weight cellar equipped (kg)	250
Dimensions H x W x D (mm)	1847 x 880 x 617***
Dimensions packaged (mm)	2000 x 970 x 700
Colours / Finishes	Standard : Red Earth, Mineral Grey Optional : 4 colors
Equipped collar weight * 122mm with roar sto	ND.

^{**}Equipped cellar weight ***+23mm with rear stop

Energy efficiency & Consumption

Cords	230V-50Hz	115V-60Hz
Type of door	Full Glass	Full Glass
Energy efficiency class	Е	1
Annual energy consumption AEC (Kwh/year)	100	85
Sound emission (dB(A))	34 (steady state)	34 (steady state)
Sound emission Class	В	/
Ambient operating temperature (°C)	5-35	5-35
Useful volume (litres)	421	

For a "service" usage, with an inner temperature between 6-9°C, we recommend to not place Royale in an ambient environment above 30°C/70% HR.

Royale, in a few words...

Why Royale?

Quite simply because it represents the best we can offer our customers in terms of performance, durability and aesthetics.



